

OAK CUMIN PLANK

Oak Cumin is a light-grey wood floor, inspired by the subtle tones of cumin, offering a soft and contemporary look. The gentle hues create a calm and refined atmosphere, while the natural wood grain adds depth and character. Perfect for modern interiors with a touch of warmth.

	PRODUCT DETAILS		
Wood Flooring / Veneer floors	LRV / LRV Std1 / LRV Std2	35 / 2.2 / 4.4	
LTCLRW4004-193 / 7393969304603	TECHNICAL PROPERTIES Emission of formaldehyde F1		
1-strip / White Oak			⊏1
Ultra matt lacquer / Stained	Moisture content	EN13183	7%±2%
Beveled 4-sided, Brushed	, , , , , , , , , , , , , , , , , , ,		>800 kg/m³
7 5/8 x 78 x 3/8"		EN13501-1	Bfl-s1
53.6 lbs			E1
28.8 sqft / 1439.7 sqft	Content PCP	CEN/TR14823	≤ 5 x 10-6n
	Breaking Strength N/mm ²	EN1533	NPD
Calm			0,15 W/mK
Woodloc® 5G	· · · · · · · · · · · · · · · · · · ·		.07 (m2K/W)
Floating, Glue-Down			Class 1
Yes		EIN530-2	
Hardwood / 0"	CARB2		Compliant
	sion crass floor		
No			
HDF	22 LY W ON OF Constant territory		
Veneer			
	LTCLRW4004-193 / 7393969304603 1-strip / White Oak Ultra matt lacquer / Stained Beveled 4-sided, Brushed 7 5/8 x 78 x 3/8" 53.6 lbs 28.8 sqft / 1439.7 sqft Calm Woodloc® 5G Floating, Glue-Down Yes Hardwood / 0" No HDF	Wood Flooring / Veneer floorsLRV / LRV Std1 / LRV Std2LTCLRW4004-193 / 7393969304603TECHNICAL PROPERTIES1-strip / White OakEmission of formaldehydeUltra matt lacquer / StainedMoisture contentBeveled 4-sided, BrushedKg/m³7 5/8 x 78 x 3/8"Reaction To Fire53.6 lbsFormaldehyde Emission28.8 sqft / 1439.7 sqftContent PCPBreaking Strength N/mm²Thermal ConductivityWoodloc® 5GThermal Resistance R-ValueFloating, Glue-DownBiological DurabilityYesCARB2Hardwood / 0"KasaNoHDF	Wood Flooring / Veneer floorsLRV / LRV Std1 / LRV Std235 / 2.2 / 4.4LTCLRW4004-193 / 7393969304603TECHNICAL PROPERTIES1-strip / White OakEmission of formaldehydeUltra matt lacquer / StainedMoisture contentEN13183Beveled 4-sided, BrushedKg/m³EN13501-153.6 lbsReaction To FireEN13501-153.6 lbsFormaldehyde EmissionEN717-128.8 sqft / 1439.7 sqftContent PCPCEN/TR14823GalmBreaking Strength N/mm²EN1533Woodloc® 5GThermal ConductivityEN12664Floating, Glue-DownBiological DurabilityEN350-2Hardwood / 0"CARB2CARB2

DETAILED DESCRIPTION

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Packages may contain start and stop boards.

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



OAK SAFFRON PLANK







OAK CLOVES PLANK



OAK PEPPER PLANK



OAK GINGER PLANK



OAK TURMERIC PLANK



OAK NUTMEG PLANK