

OAK PEPPER PLANK

This smokey oak wood floor, offers a bold and rustic design. The rich, dark tones with a deep color reminiscent of pepper are enhanced by natural knots and a textured grain. Oak Peppers rugged character adds depth and warmth, making it an ideal choice for a space with a spicy style and natural appeal.

	PRODUCT DETAILS		
Wood Floors / Veneer floors	LRV / LRV Std1 / LRV Std2	25/3/6	
LTCLRW4013-193 / 7393969304634	Warranty	15 years	
Plank / Oak			
Ultra matt lacquer / Stained	Emission of formaldehyde		E1
Develled 4 sided Drushed	Moisture content	EN13183	7%±2%
193 x 1980 x 10 mm	——— Minimun Mean Density ——— kg/m ³		>800 kg/m³
24.3 kg		FN13501-1	Bfl-s1
2.675 m ² / 133.75 m ²	Formaldehyde Emission	EN717-1	E1
	Content PCP	CEN/TR14823	≤ 5 ppm
Dynamic	Breaking Strength N/mm ²	EN1533	NPD
Woodloc® 5G	<u> </u>	FN12664	0,15 W/mK
Floating, Glue-down	Thermal Resistance R-Value		.07 (m2K/W)
Yes			Class 1
Hardwood / 0.6 mm			Compliant
			Compliant
Not resandable			
HDF			
Veneer			
	LTCLRW4013-193 / 7393969304634 Plank / Oak Ultra matt lacquer / Stained Bevelled 4-sided, Brushed 193 x 1980 x 10 mm 24.3 kg 2.675 m² / 133.75 m² Dynamic Woodloc® 5G Floating, Glue-down Yes Hardwood / 0.6 mm Not resandable HDF	Wood Floors / Veneer floorsLRV / LRV Std1 / LRV Std2LTCLRW4013-193 / 7393969304634WarrantyPlank / OakTECHNICAL PROPERTIESUltra matt lacquer / StainedEmission of formaldehydeBevelled 4-sided, BrushedMoisture content193 x 1980 x 10 mmkg/m³24.3 kgReaction To Fire2.675 m² / 133.75 m²Formaldehyde EmissionDynamicContent PCPDynamicBreaking Strength N/mm²YesBiological DurabilityHardwood / 0.6 mmCARB2Not resandableHDF	Wood Floors / Veneer floorsLRV / LRV Std1 / LRV Std225 / 3 / 6LTCLRW4013-193 / 7393969304634Warranty15 yearsPlank / OakTECHNICAL PROPERTIESUltra matt lacquer / StainedMoisture contentEN13183Bevelled 4-sided, BrushedMoisture contentEN13183193 x 1980 x 10 mmKg/m³Reaction To FireEN13501-12.675 m² / 133.75 m²Reaction To FireEN13501-1DynamicContent PCPCEN/TR14823Breaking Strength N/mm²EN1533Woodloc® 5GThermal ConductivityEN12664Floating, Glue-downThermal Resistance R-ValueYesBiological DurabilityEN350-2Hardwood / 0.6 mmCARB2CARB2

DETAILED DESCRIPTION

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: The colour matures over time

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | [©]Kährs broximate idea of the items 2025-09-01 bres only. We cannot

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



OAK TAHINI PLANK



OAK PEPPER PLANK

OAK CLOVES PLANK



OAK SESAME PLANK



OAK TURMERIC PLANK



OAK GINGER PLANK



OAK SAFFRON PLANK



OAK CARDAMOM PLANK



OAK NUTMEG PLANK



OAK CUMIN PLANK



OAK FENNEL PLANK