



R10

Suitable

Good

< 2 kV (antistatic)

Pass with good results

SAPO DBW 229-055 - 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT
Article Number / EAN Code	LTDBW2122-229-55 / 7393969303088
Design	Tile Design
Width x Length x Thickness	229 x 1219 x 2.5 mm
Weight per package	16 kg
Area per package / per	4 m ² / 265.6 m ²
pallet	
Installation method	Glue-down
Floor heating	Yes
Wear leayer thickness	0.55 mm
Warranty	30 years
TECHNICAL PROPERTIES	

	MESION	CLASS.
Ś	NA 1	100
œ	LIVI	. / ĝ
1	PASTAM	CAIDIL.
	-TAM	91

fungi



TECHNICAL PROPERTIES

DIN 51130

EN ISO 26987

EN 1815

EN 425

Slip resistance

propensity

Statical electrical

Chemical resistance

Effect of castor chair

Resistance to bacteria and

EN13501-1	Bfl-s1
	0.011 (m2K/W)
EN ISO 23999	< 0.1 %
EN ISO 105-B02	≥ 6
EN 13893	DS (>0.3)
	EN ISO 23999 EN ISO 105-B02

PRODUCT DETAILS

Other products in this collection





HUMBOLDT - DRY BACK

PLITVICE - DRY BACK

TRIGLAV - DRY BACK