



R10

Suitable

Good

< 2 kV (antistatic)

Pass with good results

HANMER DRY BACK 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS		TECHNICAL PROPERTIES
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT	Slip resistance
Article Number / EAN Code	LTDBW2010-229-5 / 7393969303118	Statical electrical
Design	Plank	propensity
Width x Length x Thickness	229 x 1219 x 2.5 mm	Chemical resistance
Weight per package	16 kg	Effect of castor chair
Area per package / per	3.9 m ² / 265.6 m ²	Resistance to bacteria and
pallet		fungi
Installation method	Glue-down	-610N CC
Floor heating	Yes	floor M1) score
Wear leayer thickness	0.55 mm	O SC3 gapes services
Warranty	30 years	_
TECHNICAL PROPERTIES		_





DIN 51130

EN ISO 26987

EN 1815

EN 425

TECHNICAL PROPERTIES		
Reaction To Fire	EN13501-1	Bfl-s1
Thermal Resistance R-Value		0.011 (m2K/W)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6

EN 13893

Slip resistance

DS (>0.3)

Other products in this collection





HUMBOLDT DRY BACK

PLITVICE DRY BACK

TRIGLAV DRY BACK