




KILSBERGEN DRY BACK 0.55 MM

PRODUCT DETAILS		TECHNICAL PROPERTIES			
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT		Slip resistance	DIN 51130	R10
Article Number / EAN Code	LTDBW2302-229-5 / 7393969303101		Statical electrical propensity	EN 1815	< 2 kV (antistatic)
Design	1-strip		Chemical resistance	EN ISO 26987	Pass with good results
Width x Length x Thickness	229 x 1219 x 2.5 mm		Resistance to bacteria and fungi		Good
Weight per package	16 kg		 		
Area per package / per pallet	3.9 m² / 265.6 m²				
Installation method	Glue-down				
Floor heating	Yes				
Wear leayer thickness	0.55 mm				
Warranty	30 years				
TECHNICAL PROPERTIES					
Reaction To Fire	EN13501-1	Bfl-s1			
Thermal Resistance R-Value	0.011 (m2K/W)				
Dimensional stability	EN ISO 23999	< 0.1 %			
Colour fastness	EN ISO 105-B02	≥ 6			
Slip resistance	EN 13893	DS (>0.3)			

Other products in this collection



SAPO DRY BACK



HANMER DRY BACK



MOESGAARD DRY BACK



FONTIN DRY BACK



THURINGIAN DRY BACK




COCONINO DRY BACK




FOLOI DRY BACK



BLAIKEN DRY BACK



KILSBERGEN DRY BACK



AKKELIS DRY BACK



STANTON DRY BACK



DURMITOR DRY BACK



CALDER DRY BACK



TIVEDEN DRY BACK



CORMORANT DRY BACK



YUKON DRY BACK



TAIGA DRY BACK



BELLUNO DRY BACK



WENTWOOD DRY BACK



SCHWARZWALD DRY BACK



SAXON DRY BACK



SAREK DRY BACK



REDWOOD DRY BACK



OULANKA DRY BACK



WHINFELL DRY BACK



HUMBOLDT DRY BACK



PLITVICE DRY BACK



TRIGLAV DRY BACK