



KILSBERGEN DRY BACK 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free. The decor features a rich variety of colors and tones, creating a visually dynamic surface.

PRODUCT DETAILS			TECHNICAL PROPERTIES
Product type / Construction	Vinyl Flooring / Dry Back LVT		Statical electrical
Article Number / EAN Code	LTDBW2302-229-5 / 7393969303101		propensity
Design	1-strip		Chemical resistance
Width x Length x Thickness	9 x 48 x 1/8"		Effect of castor chair
Weight per package	35.3 lbs		Resistance to bacteria and
Area per package / per	42 sqft / 2858.9 sqft		fungi
pallet			SION C/.
Installation method	Glue-Down		floor score
Floor heating	Yes		O account services
Wear leayer thickness	0"		
TECHNICAL PROPERTIES			
Reaction To Fire	EN13501-1	Bfl-s1	_
Thermal Resistance R-Value		0.011 (m2K/W)	_
Dimensional stability	EN ISO 23999	< 0.1 %	_
Colour fastness	EN ISO 105-B02	≥ 6	_
Slip resistance	EN 13893	DS (>0.3)	_
Slip resistance	DIN 51130	R10	

Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Chemical resistance	EN ISO 26987	Pass with good results

Suitable Effect of castor chair FN 425 Resistance to bacteria and Good fungi





Other products in this collection





HUMBOLDT DRY BACK

PLITVICE DRY BACK

TRIGLAV DRY BACK