

THURINGIAN DRY BACK 0.55 MM

EN 13893

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT		Slip resistance	DIN 51130	R10
Article Number / EAN Code	LTDBW2311-229-5 / 7393969303156		Statical electrical	EN 1815	< 2 kV (antistatic)
Design	Plank		propensity		
Width x Length x Thickness	229 x 1219 x 2.5 mm		Chemical resistance	EN ISO 26987	Pass with good results
Weight per package	16 kg		Effect of castor chair	EN 425	Suitable
Area per package / per	3.9 m ² / 265.6 m ²		Resistance to bacteria and		Good
pallet			fungi		
Installation method	Glue-down		SION CL		
Floor heating	Yes		M1) score		
Wear leayer thickness	0.55 mm		A BALEW ON OF CONTRACTOR		
Warranty	30 years		_		
TECHNICAL PROPERTIES					
Reaction To Fire	EN13501-1	Bfl-s1	_		
Thermal Resistance R-Value		0.011 (m2K/W)	_		
Dimensional stability	EN ISO 23999	< 0.1 %	_		
Colour fastness	EN ISO 105-B02	≥ 6	_		

Descriptions & Imagery

Slip resistance

www.kahrs.com | [©]Kährs 2025-09-03

DS (>0.3)

Other products in this collection







REDWOOD DRY BACK



WHINFELL DRY BACK

SAREK DRY BACK



HUMBOLDT DRY BACK

DAINTREE DRY BACK



PLITVICE DRY BACK



OULANKA DRY BACK



WAIPOUA DRY BACK



TRIGLAV DRY BACK



KOMI DRY BACK



VALDIVIAN DRY BACK