



## ASH CORAL

Ash Coral has a modern yet classic look with tones of warm white corals from sandy beaches. The characteristics of the ash enhance the impression of this matt lacquered 3-strip floor.

| PRODUCT DETAILS             |   |
|-----------------------------|---|
| Product type / Construction | Wood Floors / 3-layer parquet               |
| Article Number / EAN Code   | 133N11AKLCKW226 / 7393969304733             |
| Design / Wood Species       | 3-strip / Ash                               |
| Surface treatment /         | Matt lacquer / Stained                      |
| Natural/Stained             |   |
| Width x Length x Thickness  | 188 x 2266 x 13 mm                          |
| Weight per package / per    | 24.55 kg / 7.2 kg                           |
| m2                          |   |
| Area per package / per      | 3.41 m <sup>2</sup> / 119.35 m <sup>2</sup> |
| pallet                      |   |
| Grading                     | Lively                                      |
| Joint                       | Woodloc® 5G                                 |
| Installation method         | Floating, Glue-down                         |
| Floor heating               | Yes   |
| Wear leayer material /      | Hardwood / 2.6 mm                           |
| thickness                   |   |
| Resandable                  | 2-3 times                                   |
| Core material               | Pine/Spruce                                 |
| Backside material           | Spruce                                      |
| Hardness (Brinell) value /  | 4,0 / 2.8 - 6.2                             |
| range                       |   |

| <b>PRODI</b> | JCT | <b>DETAI</b> | LS |
|--------------|-----|--------------|----|
|--------------|-----|--------------|----|

| FRODUCT DETAILS                     |             |            |
|-------------------------------------|-------------|------------|
| LRV / LRV Std1                      | 62 / 6.7    |            |
| Warranty                            | 20 years    |            |
| TECHNICAL PROPERTIES                |             |            |
| Moisture content                    | EN13183     | 7%±2%      |
| Minimun Mean Density                |             | >500 kg/m³ |
| kg/m³                               |             |            |
| Reaction To Fire                    | EN13501-1   | Dfl-s1     |
| Formaldehyde Emission               | EN717-1     | E1         |
| Content PCP                         | CEN/TR14823 | ≤ 5 ppm    |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD        |
| Thermal Conductivity                | EN12664     | 0,11W/mK   |
| Biological Durability               | EN350-2     | Class 1    |
| CARB2                               |             | Compliant  |
| Slip resistance                     | CEN/TS15676 | NPD        |

















## DETAILED DESCRIPTION

Any naturally occuring wood colour variations allowed, from light blond to dark brown. The product includes medium sized sound and black knots/fillings. Knots and fillings may vary in size and numbers.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

## Other products in this collection









OAK CLAY

ASH CORAL

OAK SAND



OAK CHALK