



ASH CORAL

Ash Coral has a modern yet classic look with tones of warm white reminiscent of corals from tropical waters. The characteristics of ash enhance the impression of this matt lacquered 3-strip floor.

Product type / Construction Wood Flooring / 3-layer parquet Article Number / EAN Code 133N11AKLCKW226 / 7393969304733 Design / Wood Species 3-strip / Ash Surface Treatment / Matt lacquer / Stained Natural/Stained Width x Length x Thickness 188 x 2266 x 13 mm Weight per package / per 24.55 kg / 7.2 kg m2 Area per package / per 3.41 m² / 119.35 m² pallet Grading Lively Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	PRODUCT DETAILS	
Design / Wood Species 3-strip / Ash Surface Treatment / Matt lacquer / Stained Width x Length x Thickness 188 x 2266 x 13 mm Weight per package / per 24.55 kg / 7.2 kg m2 Area per package / per 3.41 m² / 119.35 m² pallet Grading Lively Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Product type / Construction	Wood Flooring / 3-layer parquet
Surface Treatment / Matt lacquer / Stained Natural/Stained Width x Length x Thickness 188 x 2266 x 13 mm Weight per package / per 24.55 kg / 7.2 kg m2 Area per package / per 3.41 m² / 119.35 m² pallet Grading Lively Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Article Number / EAN Code	133N11AKLCKW226 / 7393969304733
Natural/Stained Width x Length x Thickness	Design / Wood Species	3-strip / Ash
Width x Length x Thickness 188 x 2266 x 13 mm Weight per package / per 24.55 kg / 7.2 kg m2 Area per package / per 3.41 m² / 119.35 m² pallet Grading Lively Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Surface Treatment /	Matt lacquer / Stained
Weight per package / per 24.55 kg / 7.2 kg m2 Area per package / per 3.41 m² / 119.35 m² pallet Grading Lively Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Natural/Stained	
m2 Area per package / per 3.41 m² / 119.35 m² pallet Grading Lively Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Width x Length x Thickness	188 x 2266 x 13 mm
Area per package / per 3.41 m² / 119.35 m² pallet Grading Lively Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Weight per package / per	24.55 kg / 7.2 kg
pallet Grading Lively Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	<u>m2</u>	
Grading Lively Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Area per package / per	3.41 m ² / 119.35 m ²
Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	pallet	
Installation method Floating, Glue-down Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Grading	Lively
Floor heating Yes Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Joint	Woodloc® 5G
Wear leayer material / Hardwood / 2.6 mm thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Installation method	Floating, Glue-down
thickness Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Floor heating	Yes
Resandable 2 times Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Wear leayer material /	Hardwood / 2.6 mm
Core material Pine/Spruce Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	thickness	
Backside material Spruce Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Resandable	2 times
Hardness (Brinell) value / 4,0 / 2.8 - 6.2	Core material	Pine/Spruce
,	Backside material	Spruce
	Hardness (Brinell) value /	4,0 / 2.8 - 6.2
range	range	

Ρ	RO	DU	ICT	DE.	TAIL	S
---	----	----	-----	-----	------	---

LRV / LRV Std1	62 / 6.7	
Warranty	20 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









DETAILED DESCRIPTION

Colour change: Stained product - noticeable colour change over time.

Packages may contain start and stop boards.

Other products in this collection









OAK CLAY

ASH CORAL

OAK SAND

OAK SEED



OAK CHALK