

OAK CHALK

Oak Chalk is a gently white-colored oak floor, bringing the thoughts to the Mediterranean area with its white chalked stonewalls. This 3-strip, matt lacquered floor has a modern yet classic and timeless look.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	LRV / LRV Std1	50 / 2.7	
Article Number / EAN Code	133N14EKLCKW226 / 7393969304863	Warranty	20 years	
Design / Wood Species	3-strip / Oak	— TECHNICAL PROPERTIES		
Surface treatment / Natural/Stained	Matt lacquer / Stained	Moisture content	EN13183	7%±2%
Width x Length x Thickness	188 x 2266 x 13 mm	—— Minimun Mean Density —— kg/m³		>500 kg/m ³
Weight per package / per m2	24.55 kg / 7.2 kg	Reaction To Fire	EN13501-1	Dfl-s1
	2.44 2.440.25 2	Formaldehyde Emission	EN717-1	E1
Area per package / per	3.41 m ² / 119.35 m ²	Content PCP	CEN/TR14823	≤ 5 ppm
pallet		Breaking Strength N/mm ²	EN1533	NPD
Grading	Variation	Thermal Conductivity	EN12664	0,11W/mK
Joint	Woodloc® 5G	— Thermal Resistance R-Value		.09 (m2K/W)
Installation method	Floating, Glue-down	-	FN350-2	Class 1
Floor heating	Yes	Biological Durability	EN3DU-Z	
Wear leayer material /	Hardwood / 2.6 mm	CARB2		Compliant
thickness		Slip resistance	CEN/TS15676	NPD
Resandable	2-3 times	TSCA TITLE VI CARB P2	B BYSGUARU B BEDDININGEN	A+ score
Core material	Pine/Spruce lamella			
Backside material	Spruce	Compliant Sylvm Only	DASIA	COMMUND AY SCS Global Services





DETAILED DESCRIPTION

range

Hardness (Brinell) value /

Naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes small sound and black knots. Knots may vary in size and numbers.

Colour change: Stained product - noticeable color change over time.

3,7 / 2.2 - 5.9

Packages may contain start and stop boards.

Other products in this collection









OAK CLAY

ASH CORAL

OAK SAND



OAK CHALK