

OAK CHALK

Oak Chalk is a gently white-colored oak floor, bringing the thoughts to the Mediterranean area with its white chalked stonewalls. This 3-strip, matt lacquered floor has a modern yet classic and timeless look.

| | PRODUCT DETAILS | |
|---|--|--|
| Wood Floors / 3-layer parquet | LRV / LRV Std1 5 | 50 / 2.7 |
| 133N14EKLCKW226 / 7393969304863 | Warranty 2 | 20 year |
| 3-strip / Oak | TECHNICAL PROPERTIES | |
| Matt lacquer / Stained | | N1318 |
| | | 111310 |
| 188 x 2266 x 13 mm | • | |
| 24.55 kg / 7.2 kg | | N1350 |
| | | N717- |
| 3.41 m ² / 119.35 m ² | | EN/TR |
| | | N1533 |
| Variation | | |
| Woodloc® 5G | | N1266 |
| Floating, Glue-down | | N350- |
| Yes | | |
| Hardwood / 2.6 mm | — Slip resistance C | EN/TS |
| | TSCA de SNAN ECO. MESION CLAS | |
| 2-3 times | CARB P2 | BAST |
| Pine/Spruce | Compliant ON TO STATE OF THE ST | DASI |
| Spruce | _ | |
| | 133N14EKLCKW226 / 7393969304863 3-strip / Oak Matt lacquer / Stained 188 x 2266 x 13 mm 24.55 kg / 7.2 kg 3.41 m² / 119.35 m² Variation Woodloc® 5G Floating, Glue-down Yes Hardwood / 2.6 mm 2-3 times Pine/Spruce | Wood Floors / 3-layer parquet 133N14EKLCKW226 / 7393969304863 3-strip / Oak Matt lacquer / Stained Minimun Mean Density kg/m³ 24.55 kg / 7.2 kg Reaction To Fire Formaldehyde Emission Content PCP Variation Variation Woodloc® 5G Floating, Glue-down Yes Hardwood / 2.6 mm Pine/Spruce LRV / LRV Std1 Salary / LRV Std1 ERV / LRV Std1 Salary |

| LRV / LRV Std1 | 50 / 2.7 | |
|-------------------------------------|-------------|------------|
| Warranty | 20 years | |
| TECHNICAL PROPERTIES | 5 | |
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |











DETAILED DESCRIPTION

range

Hardness (Brinell) value /

Naturally occuring wood colour variations allowed, from light to dark brown. Sapwood will occur. The product includes small sound and black knots. Knots may vary in size and numbers.

Colour change: Stained product - noticeable color change over time.

3,7 / 2.2 - 5.9

Packages may contain start and stop boards.

Other products in this collection









OAK CLAY

ASH CORAL

OAK SAND



OAK CHALK