



CLASSIC OAK TUNDRA

PRODUCT DETAILS

Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	133N22EK1VWC226 / 7393969304788
Design / Wood Species	3-strip / Oak
Surface treatment / Natural/Stained	Matt lacquer / Stained
Width x Length x Thickness	188 x 2266 x 13 mm
Weight per package / per m2	24 kg / 7.04 kg
Area per package / per pallet	3.41 m² / 119.35 m²
Grading	Lively
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 2.6 mm
Resandable	2-3 times
Core material	Pine/Spruce lamella
Backside material	Spruce
Hardness (Brinell) value	3,7

PRODUCT DETAILS

LRV / LRV Std1	45 / 6
Warranty	20 years

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimun Mean Density	>500 kg/m³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. Will include sapwood. The product includes medium sound and black knots/fillings. Knots and fillings may vary in size and numbers.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

Other products in this collection



CLASSIC OAK TUNDRA