



# OAK INDOSSATI CONSUMER SAMPLE

PRODUCT DETAILS		Grading	Expressive
Product type / Construction	Wood Flooring / 3-layer parquet	Joint	Woodloc® 5G
Article Number	SA01-151XDDEKFHKW	Installation method	Glue-down, Floating
Design / Wood Species	1-strip / Oak	Floor heating	Yes
Surface Treatment / Natural/Stained	Oil / Stained	Wear leayer material / thickness	Hardwood / 3.5 mm
Refining Treatment	Bevelled 4-sided, Brushed, Light smoked, Handscraped	Core material	Pine/Spruce
Width x Length x Thickness	190 x 200 x 15 mm	Backside material	Veneer
		Hardness (Brinell) value / range	3,7 / 2.2 - 5.9
		Warranty	30 years

**DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.  
 The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

**Oil:** This floor should be oiled immediately after installation.

**Colour change:** Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection



OAK DECORUM



OAK DOMO



OAK DUSSATO



OAK UNICO



OAK SPARUTO



OAK INDOSSATI



OAK MAGGIORE