



OAK PORTOFINO FULL PLANK/ TILE SAMPLE

	Grading	Variation
Wood Flooring / 3-layer parquet	Joint	Woodloc® 5S
SA02-152N38EK0VKW240	Installation method	Floating, Glue-down
2-strip / Oak	Floor heating	Yes
Matt lacquer / Stained	Wear leayer material /	Hardwood / 3.5 mm
	thickness	
200 x 2423 x 15 mm	Resandable	2-3 times
	Core material	Pine/Spruce/Alder
	Hardness (Brinell) value /	3,7 / 2.2 - 5.9
	range	
	Warranty	30 years
	SA02-152N38EK0VKW240 2-strip / Oak Matt lacquer / Stained	Wood Flooring / 3-layer parquet SA02-152N38EK0VKW240 2-strip / Oak Matt lacquer / Stained Wear leayer material / thickness 200 x 2423 x 15 mm Resandable Core material Hardness (Brinell) value / range

DETAILED DESCRIPTION

Naturally occuring wood colour variations allowed, from light to dark brown. Will include sapwood. The product includes medium sound and black knots. Knots may vary in size and numbers.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection



OAK ESTORIL



OAK SORRENTO



OAK PORTOFINO



OAK BRIGHTON



ASH SKAGEN



ASH SANDVIG



ASH FALSTERBO