



LUCANIA CLS 300

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

DD	OD	пст	DFTA	VII C	

Article Number	LTCLS3001-300
Dimensions	300 x 600 mm
Weight per Package	17.6 kg
Area per Package	1.8 m ²
Area per pallet	86.4 m ²
Construction	Click 6 mm
FACTS	
FACTS Design	Stone design
	Stone design Luxury Tiles
Design	
Design Range	Luxury Tiles

TECHNICAL PROPERTIES

ECHNICAL PROPERTIES			
Application	EN ISO 10874	23/33/42	
Emission of formaldehy	rde	E1	
Reaction To Fire	EN13501-1	Bfl-s1	B _{IT} S1
Formaldehyde Emission	EN717-1	E1	
Thermal Resistance R-Value		0.035 (m2K/W)	(° ,
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with underlayment)	
Dimensional stability	EN ISO 23999	< 0.1 %	K N
Colour fastness	EN ISO 105- B02	≥ 6	7
Slip resistance	EN 13893	DS (>0.3)	975
Slip resistance	DIN 51130	R10	9 (S)
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	F

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









TECHNICAL PROPERTIES

Commercial usage classification	EN 14354:2017	Class 33	
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)	
Resistance to bacteria an	d fungi	Good	
Chemical resistance	EN ISO 26987	Pass with good results	€
Scratch resistance	EN16094	Pass with good results	

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.












Other products in this collection



Steele - Click 6 mm

Kebnekaise - Click 6 mm

Grossglockner - Click 6 mm

Lucania - Click 6 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









