






KANNUR CLW 172

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Vinyl Flooring / Click SPC LVT		Slip resistance	EN 13893	DS (>0.3)
Article Number / EAN Code	LTCLW2113-172 / 7393969111805		Slip resistance	DIN 51130	R10
Design	Tile Design		Statical electrical propensity	EN 1815	< 2 kV (antistatic)
Width x Length x Thickness	6 3/4 x 47 5/8 x 1/4"		Scratch resistance	EN16094	Pass with good results
Weight per package / per m2	35.7 lbs / 17 lbs		Chemical resistance	EN ISO 26987	Pass with good results
Area per package / per pallet	22.6 sqft / 1119.4 sqft		Effect of castor chair	EN 425	Suitable
Joint	Click5G		Resistance to bacteria and fungi		Good
Installation method	Floating		Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)
Floor heating	Yes				
Wear leayer thickness	0"				
TECHNICAL PROPERTIES					
Reaction To Fire	EN13501-1	Bfl-s1			
Thermal Resistance R-Value		0.032 (m2K/W)			
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with underlayment)			
Dimensional stability	EN ISO 23999	< 0.1 %			
Colour fastness	EN ISO 105-B02	≥ 6			





Other products in this collection



Redwood - Click 5 mm



Kannur - Click 5 mm



Saxon - Click 5 mm



Oulanka - Click 5 mm



Yukon - Click 5 mm



Sarek - Click 5 mm



Taiga - Click 5 mm



Whinfell - Click 5 mm