



KANNUR CLW 172

DESCRIPTION DU PRODU	JIT		(
Type de produit /	Sol vinyle / Click SPC LVT			
Construction			(
Code article / Code EAN	LTCLW2113-172 / 7393969111805			
Style	1-frise			
Largeur x Longueur x	172 x 1210 x 5 mm			
Épaisseur				
Poids par paquet / par m2	16,2 kg / 7,71 kg		:	
Surface par paquet / par	2,08 m ² / 104 m ²			
palette				
INFORMATIONS				
Joint d'assemblage	Click5G			
Pose	Flottante			
Chauffage au sol	Oui			
Couche d'usure épaisseur	0,3 mm			
Garantie	10 ans			
CARACTÉRISTIQUES TECHNIQUES				
Réaction au feu	EN13501-1	Bfl-s1		
Valeur Résistance		0.032 (m2K/W)		
thermique				
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with		

CARACTÉRISTIQUES TECHNIQUES

Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
Chemical resistance Resistance to bacteria and fungi	EN ISO 26987	Pass with good results Good











underlayment)

Autres produits dans cette collection



Redwood - Click 5 mm



Kannur - Click 5 mm



Saxon - Click 5 mm



Oulanka - Click 5 mm



Yukon - Click 5 mm



Sarek - Click 5 mm



Taiga - Click 5 mm



Whinfell - Click 5 mm