



## OAK TAHINI PLANK

With light silver-golden tones of Tahini this light wood floor exudes rustic charm with its natural wood grain and knots in a darker contrast. Its organic and brushed texture enhances character, ensuring each plank is distinctive and bringing a warm yet airy ambiance to any room.

| PRODUCT DETAILS             |  |
|-----------------------------|--|
| Product type / Construction | Wood Flooring / Veneer floors                |
| Article Number / EAN Code   | LTCLRW4016-193 / 7393969305303               |
| Design / Wood Species       | 1-strip / Oak                                |
| Surface Treatment /         | Oil / Stained                                |
| Natural/Stained             |  |
| Refining Treatment          | Bevelled 4-sided, Brushed                    |
| Width x Length x Thickness  | 193 x 1980 x 10 mm                           |
| Weight per package          | 24.3 kg                                      |
| Area per package / per      | 2.675 m <sup>2</sup> / 133.75 m <sup>2</sup> |
| pallet                      |  |
| Grading                     | Dynamic                                      |
| Joint                       | Woodloc® 5G                                  |
| Installation method         | Floating, Glue-down                          |
| Floor heating               | Yes  |
| Wear leayer material /      | Hardwood / 0.6 mm                            |
| thickness                   |  |
| Core material               | HDF  |
| Backside material           | Veneer                                       |
| LRV / LRV Std1 / LRV Std2   | 39 / 5 / 10                                  |

| I | F( | _H | IN | ICA | ٩L | Р | RC | P( | Εŀ | ۲I | IF? | 5 |
|---|----|----|----|-----|----|---|----|----|----|----|-----|---|
|   |    |    |    |     |    |   |    |    |    |    |     |   |

| Emission of formaldehyde            |             | E1          |
|-------------------------------------|-------------|-------------|
| Moisture content                    | EN13183     | 7%±2%       |
| Minimun Mean Density                |             | >800 kg/m³  |
| kg/m³                               |             |             |
| Reaction To Fire                    | EN13501-1   | Bfl-s1      |
| Formaldehyde Emission               | EN717-1     | E1          |
| Content PCP                         | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD         |
| Thermal Conductivity                | EN12664     | 0,15 W/mK   |
| Thermal Resistance R-Value          | !           | .07 (m2K/W) |
| Biological Durability               | EN350-2     | Class 1     |
| CARB2                               |             | Compliant   |
|                                     |             |             |





## DETAILED DESCRIPTION

 $\label{Oil:This floor} \textbf{Oil:} \ \ \textbf{This floor should be oiled immediately after installation}.$ 

Packages may contain start and stop boards.

## Other products in this collection

OAK CLOVES PLANK



OAK GINGER PLANK

OAK NUTMEG PLANK