



E1

7%±2%

Bfl-s1

E1

NPD

Class 1

Compliant

 $> 800 \text{ kg/m}^3$ 

≤ 5 x 10-6n

0,15 W/mK

.07 (m2K/W)

# OAK FENNEL PLANK

Inspired by the color of dried fennel-seeds Oak Fennel ranges from faint tan to a light golden beige brown, contrasting with the darker knots and grain creating a natural, rustic design. The brushing, in combination with the oiled surface of each plank highlights the natural texture of this floor for a natural appeal.

#### Product type / Construction Wood Flooring / Veneer floors Article Number / EAN Code LTCLRW4015-193 / 7393969305297 Design / Wood Species 1-strip / Oak Surface Treatment / Oil / Stained Natural/Stained **Refining Treatment** Bevelled 4-sided, Brushed Width x Length x Thickness 193 x 1980 x 10 mm Weight per package 24.3 kg Area per package / per 2.675 m<sup>2</sup> / 133.75 m<sup>2</sup> pallet Grading Dynamic Joint Woodloc® 5G Installation method Floating, Glue-down Floor heating Yes

Hardwood / 0.6 mm

OR DATES BUT	
4	
A 10 C	
A 0 0	



**TECHNICAL PROPERTIES** 

EN13183

EN13501-1

CEN/TR14823

EN717-1

EN1533

EN12664

EN350-2

Emission of formaldehyde

Minimun Mean Density

Formaldehyde Emission

Breaking Strength N/mm<sup>2</sup>

Thermal Resistance R-Value

Thermal Conductivity

**Biological Durability** 

Moisture content

Reaction To Fire

Content PCP

kg/m<sup>3</sup>

# MAD C

CARB2

#### DETAILED DESCRIPTION

LRV / LRV Std1 / LRV Std2

Wear leayer material /

thickness

Core material
Backside material

**PRODUCT DETAILS** 

Oil: This floor should be oiled immediately after installation.

HDF

Veneer

32/5/10

Packages may contain start and stop boards.

### Other products in this collection

OAK CLOVES PLANK



OAK GINGER PLANK

OAK NUTMEG PLANK