



OAK SESAME PLANK

Oak Sesame Plank is a natural, unstained oak wood floor with rich, dark golden tones that complement the inherent cracks and knots. The brushed surface, paired with the oiled treatment, creates a soft texture that adds warmth and comfort to any room with its authentic oak look and feel.

PRODUCT DETAILS		PRODUCT DETA
Product type / Construction	Wood Floors / Veneer floors	LRV / LRV Std1 / LF
Article Number / EAN Code	LTCLRW4014-193 / 7393969305280	Warranty
Design / Wood Species	Plank / Oak	— TECHNICAL PRO
Surface treatment /	Oil / Natural	Emission of formal
Natural/Stained		— Moisture content
Design features	Bevelled 4-sided, Brushed	— Minimun Mean De
Width x Length x Thickness	193 x 1980 x 10 mm	—— kg/m³
Weight per package	24.3 kg	
Area per package / per	2.675 m ² / 133.75 m ²	
pallet		Formaldehyde Em
Grading	Dynamic	Content PCP
Joint	Woodloc® 5G	Breaking Strength
Installation method	Floating, Glue-down	Thermal Conductiv
Floor heating	Yes	Thermal Resistanc
Wear leayer material /	Hardwood / 0.6 mm	Biological Durabilit
thickness	Hardwood / 0.0 Hilli	CARB2
Resandable	Not resandable	
Core material	HDF	B BYGGVARU BEDOMININGEN
Backside material	Veneer	

Р	RO	DU	ICT	DE	ΓAΙ	LS

LRV / LRV Std1 / LRV Std2	36 / 5.9 / 11.8	
Warranty	15 years	
TECHNICAL PROPERTIES	5	
Emission of formaldehyde		E1
Moisture content	EN13183	7%±2%
Minimun Mean Density		>800 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Bfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,15 W/mK
Thermal Resistance R-Value	2	.07 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant





DETAILED DESCRIPTION

Oil: This floor should be oiled immediately after installation.

Colour change: The colour matures over time Packages may contain start and stop boards.

Other products in this collection

OAK CLOVES PLANK



OAK GINGER PLANK

OAK NUTMEG PLANK