

MAKALU CLS 300

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and Planks	s / Click SPC LVT	Thermal Resistance R-Value		0.035 (m2K/W)
Article Number / EAN Code	LTCLS3007-300 / 73939691	10280	Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
Design	Tile Design		_		underlayment)
Width x Length x Thickness	300 x 600 x 6 mm		Dimensional stability	EN ISO 23999	< 0.1 %
Weight per package / per	17.6 kg / 9.78 kg		Colour fastness	EN ISO 105-B02	≥6
m2			Slip resistance	EN 13893	DS (>0.3)
Area per package / per	1.8 m² / 86.4 m²		Slip resistance	DIN 51130	R10
pallet			Statical electrical	EN 1815	< 2 kV (antistatic)
Joint	Click5G		propensity		
Installation method	Floating		Scratch resistance	EN16094	Pass with good results
Floor heating	Yes		Chemical resistance	EN ISO 26987	Pass with good results
Wear leayer thickness	0.55 mm		Resistance to bacteria and		Good
Warranty	30 years		fungi		
TECHNICAL PROPERTIES		Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE	
Application	EN ISO 10874	23/33/42	-		underlayment)
Emission of formaldehyde		E1	Commercial usage	EN 14354:2017	Class 33
Reaction To Fire	EN13501-1	Bfl-s1	- classification		
Formaldehyde Emission	EN717-1	E1	- floor ((R THAL AT	0

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kahrs (UK) Ltd | www.kahrs.com | [©]Kährs, United Kingdom & Ireland 2025-08-15

Other products in this collection



KILIMANJARO - CLICK 6 MM





MAKALU - CLICK 6 MM





MATTERHORN - CLICK 6 MM





SCHWARZHORN - CLICK 6 MM



STEELE - CLICK 6 MM

KEBNEKAISE - CLICK 6 MM

GROSSGLOCKNER - CLICK 6 MM LUCANIA - CLICK 6 MM