



# MAKALU CLS 300

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS	TECHNICAL PROPERTIES

Article Number	LTCLS3007-300	Application	EN ISO 10874	23/33/42	
Dimensions	300 x 600 mm			E1	
Weight per Package	17.6 kg	Emission of formaldehy	Emission of formaldehyde		
Area per Package	1.8 m <sup>2</sup>	Reaction To Fire	EN13501-1	Bfl-s1	B <sub>H</sub> s1
Area per pallet	86.4 m <sup>2</sup>	Formaldehyde Emission	EN717-1	E1	
	Click 6 mm	Thermal Resistance R-\	Thermal Resistance R-Value		-
FACTS		Residual indentation	EN ISO	< 0.2 mm (*with underlayment	:)
Design	Stone design		24343-1		
Range	Luxury Tiles	Dimensional stability	EN ISO 23999	< 0.1 %	KN
Collection	Click 6 mm Stone Collection	Colour fastness	EN ISO 105-	> 6	<b>3</b> 70
Joint	Click5G	Colour lastifess	B02	20	
Floor heating	Yes	Slip resistance	EN 13893	DS (>0.3)	975
		Slip resistance	DIN 51130	R10	925
		Statical electrical propensity	EN 1815	< 2 kV (antistatic)	Ŧ

#### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









#### **TECHNICAL PROPERTIES**

Scratch resistance	EN16094	Pass with good results	
Chemical resistance	EN ISO 26987	Pass with good results	<b>*</b>
Resistance to bacteria an	d fungi	Good	
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE underlayment)	
Commercial usage classification	EN 14354:2017	Class 33	

### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.











## Other products in this collection



#### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









