



REDWOOD CLW 172

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS		TECHNICAL PROPERTIES
Product type / Construction	Luxury Vinyl Tiles / Click 5 mm	Slin resistance

Product type / Construction	Luxury Vinyl Tiles / Click 5 mm	Slip resistance	EN 13893	DS (>0.3)
Article Number / EAN Code	LTCLW2101-172 / 7393969111782	Slip resistance	DIN 51130	R10
Design	Wood design	Statical electrical	EN 1815	< 2 kV (antistation
Width x Length x Thickness	172 x 1210 x 5 mm	propensity		
Weight per package / per	16.2 kg / 7.71 kg	Scratch resistance	EN16094	Pass with good
m2		Chemical resistance	EN ISO 26987	Pass with good
Area per package / per	2.1 m ² / 104 m ²	Resistance to bacteria and		Good
pallet		fungi		
Joint	Click5G	Impact sound reduction	EN ISO 10140	20 ∆ Lw dB (IXPE
Installation method	Floating			underlayment)
Floor heating	Yes	SION CC.	HAI	
Wear leayer thickness	0.3 mm	M1) score		Tomas (TA)











TECHNICAL PROPERTIES

Reaction To Fire	EN13501-1	Bfl-s1
Thermal Resistance R-Value		0.032 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6

results results

Other products in this collection

