



# REDWOOD CLW 172

DESCRIZIONE DEL PRODOTTO				
Codice articolo / Codice	LTCLW2101-172 / 7393969111782			
EAN				
Design	1 Listello			
Larghezza x Lunghezza x	172 x 1210 x 5 mm			
Spessore				
Peso per confezione / per	16,2 kg / 7,71 kg			
m2				
Mg. per confezione / pr	2.08 m <sup>2</sup> / 104 m <sup>2</sup>			

Spessore		
Peso per confezione / per	16,2 kg / 7,71 kg	
m2		
Mq. per confezione / pr	2,08 m <sup>2</sup> / 104 m <sup>2</sup>	
pallet		

### INFORMAZIONI

Incastro	Click5G
Metodi di posa	Flottante
Riscaldamento a pavimento	Si
Strato superficiale spessore	0,3 mm

#### CARATTERISTICHE TECNICHE

CANATTERISTICITE TECNICITE			
Classe di reazione al fuoco	EN13501-1	Bfl-s1	
Resistenza termica valore R		0.032 (m2K/W)	
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with	
		underlayment)	
Dimensional stability	EN ISO 23999	< 0.1 %	
Test Colour fastness	EN ISO 105-B02	≥ 6	

#### CARATTERISTICHE TECNICHE

Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 <b>Δ</b> Lw dB (IXPE
		underlayment)









## Altri prodotti di questa collezione



Redwood - Click 5 mm



Kannur - Click 5 mm



Saxon - Click 5 mm



Oulanka - Click 5 mm



Yukon - Click 5 mm



Sarek - Click 5 mm



Taiga - Click 5 mm



Whinfell - Click 5 mm