



TAIGA CLW 172

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

ווווואא	JCT DETA	711 <

TECHNICAL PROPERTIES

TRODUCT DETAILS		TECHNICAL FROM EIGHES		
Product type / Construction	Luxury Vinyl Tiles / Click 5 mm	Slip resistance	EN 13893	DS (>0.3)
Article Number / EAN Code	LTCLW2115-172 / 7393969111744	Slip resistance	DIN 51130	R10
Design	Wood design	Statical electrical	EN 1815	< 2 kV (antistatic)
Width x Length x Thickness	172 x 1210 x 5 mm	propensity		
Weight per package / per	16.2 kg / 7.71 kg	Scratch resistance	EN16094	Pass with good results
m2		Chemical resistance	EN ISO 26987	Pass with good results
Area per package / per	2.1 m ² / 104 m ²	Effect of castor chair	EN 425	Suitable
pallet		Resistance to bacteria and		Good
Joint	Click5G	fungi		
Installation method	Floating	Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
Floor heating	Yes			underlayment)
Wear leayer thickness	0.3 mm	GOON CK	THALO	











TECHNICAL PROPERTIES

Reaction To Fire	EN13501-1	Bfl-s1
Thermal Resistance R-Value		0.032 (m2K/W)
Residual indentation EN ISO		< 0.2 mm (*with
24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6

Other products in this collection

