

TAIGA CLW 172

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS		TECHNICAL PROPERTIES			
Article Number	LTCLW2115-172	Reaction To Fire	EN13501-1	Bfl-s1	Birst
Dimensions	172 x 1210 mm	Thermal Resistance R-Value		0.032 (m2K/W)	(***
Weight per Package	16.2 kg	Residual indentation	EN ISO 24343-1	< 0.2 mm (*with underlayment)	:) ^[]
Area per Package	2.1 m ²				
Area per pallet	104 m ²	Dimensional stability	EN ISO 23999	< 0.1 %	רא א
FACTS	Click 5 mm	Colour fastness	EN ISO 105- B02	≥ 6	37
Design	Wood design	Slip resistance	EN 13893	DS (>0.3)	Ten Is
Collection	Click 5 mm Wood Collection	Slip resistance	DIN 51130	R10	NA IS
Joint	Click5G	Statical electrical	EN 1815	< 2 kV (antistatic)	Ż
Floor heating	Yes	propensity			
	5 mm	Scratch resistance	EN16094	Pass with good results	P
		Chemical resistance	EN ISO 26987	Pass with good results	\$ 0

Resistance to bacteria and fungi Good

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



TECHNICAL PROPERTIES

Impact sound	EN ISO	20 ΔLw dB (IXPE
reduction	10140	underlayment)

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



Other products in this collection




Wentwood - Click 5 mm



Kannur - Click 5 mm

Yukon - Click 5 mm





Saxon - Click 5 mm



Sarek - Click 5 mm



Schwarzwald - Click 5 mm



Belluno - Click 5 mm



Taiga - Click 5 mm



Niagara - Click 5 mm



Oulanka - Click 5 mm



Whinfell - Click 5 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

