



TAIGA CLW 172

PRODUCT DETAILS

TECHNICAL PROPERTIES

LTCLW2115-172	Reaction To Fire	EN13501-1	Bfl-s1	B _{IT} 51
6 3/4 x 47 5/8 "	Thermal Resistance R-Value		0.032 (m2K/W)	
35.7 lbs	Residual indentation	EN ISO	< 0.2 mm (*with underlayment)	
22.6 sqft		24343-1		
1119.4 sqft	Dimensional stability	EN ISO 23999	< 0.1 %	K N
Click 5 mm	Colour fastness	EN ISO 105-	≥ 6	P
			PC (-0.2)	(%S)
Wood design	Slip resistance	EN 13893	DS (>0.3)	NS.
Luxury Tiles	Slip resistance	DIN 51130	R10	DS
Click 5 mm Wood Collection	Statical electrical propensity	EN 1815		Ĝ
Click5G				
Yes	Scratch resistance	EN16094	Pass with good results	
	Chemical resistance	EN ISO 26987	Pass with good results	€
	Resistance to bacteria and fungi		Good	
	6 3/4 x 47 5/8 " 35.7 lbs 22.6 sqft 1119.4 sqft Click 5 mm Wood design Luxury Tiles Click 5 mm Wood Collection Click5G	6 3/4 x 47 5/8 " Thermal Resistance R-V 35.7 lbs Residual indentation Dimensional stability Click 5 mm Colour fastness Wood design Luxury Tiles Click 5 mm Wood Collection Click 5 mm Wood Collection	Thermal Resistance R-Value 35.7 lbs Residual indentation 22.6 sqft Dimensional stability Click 5 mm Colour fastness EN ISO 23999 Colour fastness EN ISO 105-802 Slip resistance EN 13893 Luxury Tiles Slip resistance DIN 51130 Click 5 mm Wood Collection Click5G Yes Chemical resistance EN 16094 Chemical resistance EN ISO 26987	Thermal Resistance R-Value 0.032 (m2K/W) 35.7 lbs Residual indentation EN ISO 24343-1 1119.4 sqft Dimensional stability EN ISO 23999 Click 5 mm Colour fastness EN ISO 105- B02 Wood design Luxury Tiles Slip resistance DIN 51130 R10 Click 5 mm Wood Collection Click 6 mm Wood Collection Click 7 mm Wood Collection Click 8 mm Wood Collection Click 9 mm W

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









TECHNICAL PROPERTIES

Impact soundEN ISO20 ΔLw dB (IXPEreduction10140underlayment)



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.











Other products in this collection



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









