



# CALDER CHW 120

The Kährs Luxury Tiles Click collection feature a range of narrower and shorter boards – L (left) and R (right) boards – specially designed for herringbone patterns. They are installed using high quality Click system to ensure stability. Please note that these floors don't come with sound reducing backing, as they only measure 5 mm. They come in eight beautiful wood designs, in colours ranging from light to dark.












## PRODUCT DETAILS

Article Number	LTCHW2008R120
Dimensions	120 x 720 mm
Construction	Click Herringbone

## FACTS

Design	Wood herringbone design
Range	Luxury Tiles
Collection	Click Herringbone Collection
Joint	Click5Gi
Floor heating	Yes
Thickness	5 mm
Installation method	Floating


## TECHNICAL PROPERTIES

Reaction To Fire	EN13501-1	Bfl-s1	
Thermal Resistance R-Value	0.032 (m2K/W)		
Residual indentation EN ISO 24343-1	< 0.2 mm (*with underlayment)		
Dimensional stability	EN ISO 23999	< 0.1 %	
Colour fastness	EN ISO 105-B02	≥ 6	
Slip resistance	EN 13893	DS (>0.3)	
Slip resistance	DIN 51130	R10	
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	
Scratch resistance	EN16094	Pass with good results	
Chemical resistance	EN ISO 26987	Pass with good results	
Effect of castor chair	EN 425	Suitable	

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## TECHNICAL PROPERTIES

<b>Resistance to bacteria and fungi</b>		Good
<b>Impact sound reduction</b>	EN ISO 10140	20 ΔLw dB (IXPE underlayment) 

## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



27.03.2023

AB GUSTAF KÄHR | [www.kahrs.com](http://www.kahrs.com) | © Kährs 2023

## Other products in this collection



Sarek Herringbone



Saxon Herringbone



Belluno Herringbone



Tongass Herringbone



Redwood Herringbone



Calder Herringbone



Taiga Herringbone



Whinfell Herringbone

### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*

