



# CALDER CHW 120

The Kährs Luxury Tiles Click collection feature a range of narrower and shorter boards – L (left) and R (right) boards – specially designed for herringbone patterns. They are installed using high quality Click system to ensure stability. Please note that these floors don't come with sound reducing backing, as they only measure 5 mm. They come in eight beautiful wood designs, in colours ranging from light to dark.

| PRODUCT DETAILS     |                              | TECHNICAL PROPERTIES             |                    |                              |                     |
|---------------------|------------------------------|----------------------------------|--------------------|------------------------------|---------------------|
| Article Number      | LTCHW2008L120                | Reaction To Fire                 | EN13501-1          | Bfl-s1                       | B <sub>IT'</sub> =1 |
| Dimensions          | 120 x 720 mm                 | Thermal Resistance R-Value       |                    | 0.032 (m2K/W)                | E                   |
| Construction        | Click Herringbone            | Residual indentation             | EN ISO<br>24343-1  | < 0.2 mm (*with underlayment | <u>.</u> )          |
| PACTS Design        | Wood herringbone design      | Dimensional stability            | EN ISO<br>23999    | < 0.1 %                      | K N                 |
| Range               | Luxury Tiles                 | Colour fastness                  | EN ISO 105-<br>B02 | ≥ 6                          | <b>\$</b>           |
| Collection          | Click Herringbone Collection |                                  | B02                |                              |                     |
| Joint               | Click5Gi                     | Slip resistance                  | EN 13893           | DS (>0.3)                    | OS-                 |
| Floor heating       | Yes                          | Slip resistance                  | DIN 51130          | R10                          | 18 No.              |
|                     | 5 mm                         | Statical electrical              | EN 1815            | < 2 kV (antistatic)          | F                   |
| Installation method | Floating                     | propensity                       |                    |                              |                     |
|                     | 110000110                    | Scratch resistance               | EN16094            | Pass with good results       |                     |
|                     |                              | Chemical resistance              | EN ISO<br>26987    | Pass with good results       | <b>€</b>            |
|                     |                              | Resistance to bacteria and fungi |                    | Good                         |                     |

#### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









#### **TECHNICAL PROPERTIES**

Impact soundEN ISO20 ΔLw dB (IXPEreduction10140underlayment)



### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.











## Other products in this collection



### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.









