



SAXON CHW 120

The Kährs Luxury Tiles Click collection feature a range of narrower and shorter boards – L (left) and R (right) boards – specially designed for herringbone patterns. They are installed using high quality Click system to ensure stability. Please note that these floors don't come with sound reducing backing, as they only measure 5 mm. They come in eight beautiful wood designs, in colours ranging from light to dark.

PRODUCT DETAILS

| | |
|----------------|-------------------|
| Article Number | LTCHW2109L120 |
| Dimensions | 120 x 720 mm |
| Construction | Click Herringbone |

FACTS

| | |
|---------------------|------------------------------|
| Design | Wood herringbone design |
| Range | Luxury Tiles |
| Collection | Click Herringbone Collection |
| Joint | Click5Gi |
| Floor heating | Yes |
| | 5 mm |
| Installation method | Floating |

TECHNICAL PROPERTIES

| | | | |
|----------------------------------|----------------|-------------------------------|---|
| Reaction To Fire | EN13501-1 | Bfl-s1 |  |
| Thermal Resistance R-Value | | 0.032 (m2K/W) |  |
| Residual indentation | EN ISO 24343-1 | < 0.2 mm (*with underlayment) |  |
| Dimensional stability | EN ISO 23999 | < 0.1 % |  |
| Colour fastness | EN ISO 105-B02 | ≥ 6 |  |
| Slip resistance | EN 13893 | DS (>0.3) |  |
| Slip resistance | DIN 51130 | R10 |  |
| Statical electrical propensity | EN 1815 | < 2 kV (antistatic) |  |
| Scratch resistance | EN16094 | Pass with good results |  |
| Chemical resistance | EN ISO 26987 | Pass with good results |  |
| Resistance to bacteria and fungi | | Good | |

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



TECHNICAL PROPERTIES

| | | | |
|------------------------|--------------|-------------------------------|---|
| Impact sound reduction | EN ISO 10140 | 20 ΔLw dB (IXPE underlayment) |  |
|------------------------|--------------|-------------------------------|---|

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



Other products in this collection



Sarek Herringbone



Saxon Herringbone




Belluno Herringbone



Tongass Herringbone



Redwood Herringbone



Calder Herringbone



Taiga Herringbone



Whinfell Herringbone

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.