



OAK DUBLIN ULTRA MATT NARROW

The light honey nuances in this single-strip oak floor from the Capital Collection range from faint tan to pale golden brown, giving it an even colouring. Only the finest quality oak timber is used, and each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The light-absorbing, ultra-matt lacquer finish creates the impression of newly sawn timber, effectively eliminating glare while protecting the wood from daily wear. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

| PRODUCT DETAILS | | |
|-----------------------------|--|--|
| Product type / Construction | Wood Floors / 3-layer parquet | |
| Article Number / EAN Code | 151N45EK04KW200 / 7393969305532 | |
| Design / Wood Species | 1-strip / Oak | |
| Surface treatment / | Ultra matt lacquer / Natural | |
| Natural/Stained | | |
| Design features | Microbevelled 4-sided, Brushed | |
| Width x Length x Thickness | 151 x 2000 x 15 mm | |
| Weight per package / per | 15 kg / 8.15 kg | |
| m2 | | |
| Area per package / per | 1.81 m ² / 97.74 m ² | |
| pallet | | |
| Grading | Calm | |
| Joint | Woodloc® 5S | |
| Installation method | Floating, Glue-down | |
| Floor heating | Yes | |
| Wear leayer material / | Hardwood / 3.5 mm | |
| thickness | | |
| Resandable | 2-3 times | |
| Core material | Pine/Spruce lamella | |
| Hardness (Brinell) value / | 3,7 / 2.2 - 5.9 | |
| range | | |

| PRODUCT | DETAILS |
|---------|---------|
|---------|---------|

| LRV / LRV Std1 | 33 / 4.7 | |
|----------------------------|-------------|-------------|
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | 5 | |
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Thermal Resistance R-Value | 2 | .11 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| | | |



Slip resistance







CEN/TS15676



NPD

DETAILED DESCRIPTION

Even colour with minor variations

Small sized knots in limited numbers allowed.

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Descriptions & Imagery

Other products in this collection







OAK PARIS ULTRA MATT



OAK DUBLIN ULTRA MATT NARROW



OAK PARIS ULTRA MATT NARROW / HONEY OAT













OAK PARIS OILED

OAK DUBLIN OILED