



SAXON CLICK 5 MM

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS

TECHNICAL PROPERTIES

Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT	Colour fastness	Е
Article Number / EAN Code	LTCLW2109-172 / 7393969111768	Slip resistance	Е
Design	Plank	Slip resistance	
Width x Length x Thickness	172 x 1210 x 5 mm	Statical electrical	Е
Weight per package / per	16.2 kg / 7.71 kg	propensity	
m2		Scratch resistance	Е
Area per package / per	2.08 m ² / 104 m ²	Chemical resistance	Е
pallet		Effect of castor chair	Е
Joint	Click5G	Resistance to bacteria and	
Installation method	Floating	fungi	
Floor heating	Yes	Impact sound reduction	Е
Wear leayer thickness	0.3 mm		
Warranty	10 years	cion ci	

Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
		underlayment)











TECHNICAL PROPERTIES

Reaction To Fire	EN13501-1	Bfl-s1
Thermal Resistance R-Value		0.032 (m2K/W)
Residual indentation EN ISO		< 0.2 mm (*with
24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %

Other products in this collection



REDWOOD CLICK 5 MM



KANNUR CLICK



SAXON CLICK 5 MM



OULANKA CLICK 5 MM



YUKON CLICK



SAREK CLICK 5 MM



TAIGA CLICK 5 MM



WHINFELL CLICK 5 MM