



6%±1% $>800 \text{ kg/m}^3$

Cfl-s1 Ε1

≤ 5 ppm NPD 0,14 W/mK Class 1 Compliant

OAK CHAMOMILLE HERRINGBONE LEFT

Embrace the beauty of natural oak with a floor that brings warmth, brightness, and elegance to your home. The brushed surface highlights the wood's authentic texture, while the ultra matt finish softens light for a modern, calming feel. In a classic herringbone pattern, it adds timeless charm and refined style to any space.

PRODUCT DETAILS **TECHNICAL PROPERTIES**

Product type / Construction	Wood Floors / Veneer floors	Moisture content	EN13183
Article Number / EAN Code	LTCLRW5001L-121 / 7393969305624	Minimun Mean Density	
Design / Wood Species	Herringbone / Oak	kg/m³	
Surface treatment /	Ultra matt lacquer / Natural	Reaction To Fire	EN13501-1
Natural/Stained		Formaldehyde Emission	EN717-1
Design features	Bevelled 4-sided, Brushed	Content PCP	CEN/TR14823
Width x Length x Thickness	121 x 593 x 10 mm	Breaking Strength N/mm ²	EN1533
Weight per package	6.7 kg	Thermal Conductivity	EN12664
Area per package / per	0.789 m ² / 99.45 m ²	Biological Durability	EN350-2
pallet		CARB2	
Grading	Calm (City)	OON C	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Installation method	Floating, Glue-down	** M1> *** BYGGVARU	floor score
Floor heating	Yes	A A A L	C SCS Global Services
Wear leayer material /	Hardwood / 0.6 mm		
thickness			
Core material	HDF		



DETAILED DESCRIPTION

Backside material LRV / LRV Std1 / LRV Std2

Warranty

Ultra matt lacquer: The appearance of the matte surface may vary due to different light sources and angles.

Colour change: The colour matures over time Packages may contain start and stop boards.

Veneer

38 / 4.3 / 8.6 15 years

Descriptions & Imagery

Other products in this collection







OAK GINSENG HERRINGBONE



OAK MINT HERRINGBONE



OAK CHAMOMILLE HERRINGBONE