



## KEBNEKAISE CLS 300

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		
Article Number / EAN Code	LTCLS3005-300 / 7393969110266		
Design	Tile Design		
Width x Length x Thickness	300 x 600 x 6 mm		
Weight per package / per	17.6 kg / 9.78 kg		
m2			
Area per package / per	1.8 m <sup>2</sup> / 86.4 m <sup>2</sup>		
pallet			
Joint	Click5G		
Installation method	Floating		
Floor heating	Yes		
Wear leayer thickness	0.55 mm		
Warranty	30 years		
TECHNICAL PROPERTIES			
Application	EN ISO 10874	23/33/42	
Emission of formaldehyde		E1	
Reaction To Fire	EN13501-1	Bfl-s1	
Formaldehyde Emission	EN717-1	E1	

## **TECHNICAL PROPERTIES**

Residual indentation EN ISO 24343-1 < 0.2 mm (*with underlayment)  Dimensional stability EN ISO 23999 < 0.1 %  Colour fastness EN ISO 105-B02 ≥ 6  Slip resistance EN 13893 DS (>0.3)  Slip resistance DIN 51130 R10  Statical electrical EN 1815 < 2 kV (antistatic)  propensity  Scratch resistance EN16094 Pass with good results  Chemical resistance EN ISO 26987 Pass with good results  Resistance to bacteria and Good	Thermal Resistance R-Value		0.035 (m2K/W)
Dimensional stabilityEN ISO 23999< 0.1 %	Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
Colour fastness EN ISO 105-B02 ≥ 6  Slip resistance EN 13893 DS (>0.3)  Slip resistance DIN 51130 R10  Statical electrical EN 1815 < 2 kV (antistatic)  propensity  Scratch resistance EN16094 Pass with good results  Chemical resistance EN ISO 26987 Pass with good results  Resistance to bacteria and Good			underlayment)
Slip resistance EN 13893 DS (>0.3)  Slip resistance DIN 51130 R10  Statical electrical EN 1815 < 2 kV (antistatic)  propensity  Scratch resistance EN16094 Pass with good results  Chemical resistance EN ISO 26987 Pass with good results  Resistance to bacteria and Good	Dimensional stability	EN ISO 23999	< 0.1 %
Slip resistance DIN 51130 R10 Statical electrical EN 1815 < 2 kV (antistatic) propensity Scratch resistance EN16094 Pass with good results Chemical resistance EN ISO 26987 Pass with good results Resistance to bacteria and Good	Colour fastness	EN ISO 105-B02	≥ 6
Statical electrical EN 1815 < 2 kV (antistatic)  propensity  Scratch resistance EN16094 Pass with good results  Chemical resistance EN ISO 26987 Pass with good results  Resistance to bacteria and Good	Slip resistance	EN 13893	DS (>0.3)
propensity  Scratch resistance EN16094 Pass with good results  Chemical resistance EN ISO 26987 Pass with good results  Resistance to bacteria and Good	Slip resistance	DIN 51130	R10
Scratch resistanceEN16094Pass with good resultsChemical resistanceEN ISO 26987Pass with good resultsResistance to bacteria andGood	Statical electrical	EN 1815	< 2 kV (antistatic)
Chemical resistance EN ISO 26987 Pass with good results Resistance to bacteria and Good	propensity		
Resistance to bacteria and Good	Scratch resistance	EN16094	Pass with good results
	Chemical resistance	EN ISO 26987	Pass with good results
	Resistance to bacteria and		Good
tungi	fungi		
Impact sound reduction EN ISO 10140 20 ΔLw dB (IXPE	Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE
underlayment)			underlayment)
Commercial usage EN 14354:2017 Class 33	Commercial usage	EN 14354:2017	Class 33
classification	classification		











## Other products in this collection

STEELE - CLICK 6 MM



GROSSGLOCKNER - CLICK 6 MM LUCANIA - CLICK 6 MM

KEBNEKAISE - CLICK 6 MM