



KEBNEKAISE CLS 300

The Kährs Luxury Tiles Click floors has been designed for home and public environments that require floors with adhesive-free installation that are both beautiful and tough. They come in a variety of wood and stone designs. Maximum durability and stability is achieved through the rigid core and the unique 5G locking technology, enabling easy installation by clicking the tiles together. The Click floors are made from virgin vinyl with a rigid core. All floors in the collection have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear and tear, scratching and water. They can be installed on an existing floor, making the Click floors ideal to use in renovation projects or when you want to retain the existing floor. Just like all our other Luxury Tiles floors, they are phthalate-free.

| PRODUCT DETAILS | | | ٦ |
|-----------------------------|---------------------------------|---------------|----------|
| Product type / Construction | Luxury Vinyl Tiles / Click 6 mm | | F |
| Article Number / EAN Code | LTCLS3005-300 / 7 | 393969110266 | |
| Design | Stone design | | |
| Width x Length x Thickness | 300 x 600 x 6 mm | | (|
| Weight per package / per | 17.6 kg / 9.78 kg | | |
| m2 | | | 9 |
| Area per package / per | 1.8 m² / 86.4 m² | | |
| pallet | | | ŗ |
| Joint | Click5G | | |
| Installation method | Floating | | |
| Floor heating | Yes | | F |
| Wear leayer thickness | 0.55 mm | | f |
| TECHNICAL PROPERTIES | | | i |
| Application | EN ISO 10874 | 23/33/42 | |
| Emission of formaldehyde | | E1 | — (|
| Reaction To Fire | EN13501-1 | Bfl-s1 | <u> </u> |
| Formaldehyde Emission | EN717-1 | E1 | |
| Thermal Resistance R-Value | | 0.035 (m2K/W) | |

TECHNICAL PROPERTIES

| Residual indentation | EN ISO 24343-1 | < 0.2 mm (*with |
|----------------------------|----------------|-------------------------|
| | | underlayment) |
| Dimensional stability | EN ISO 23999 | < 0.1 % |
| Colour fastness | EN ISO 105-B02 | ≥ 6 |
| Slip resistance | EN 13893 | DS (>0.3) |
| Slip resistance | DIN 51130 | R10 |
| Statical electrical | EN 1815 | < 2 kV (antistatic) |
| propensity | | |
| Scratch resistance | EN16094 | Pass with good results |
| Chemical resistance | EN ISO 26987 | Pass with good results |
| Resistance to bacteria and | | Good |
| fungi | | |
| Impact sound reduction | EN ISO 10140 | 20 Δ Lw dB (IXPE |
| | | underlayment) |
| Commercial usage | EN 14354:2017 | Class 33 |
| classification | | |
| con o | ANA MANA | |











Other products in this collection





Makalu - Click 6 mm



Matterhorn - Click 6 mm



Schwarzhorn - Click 6 mm



Steele - Click 6 mm



Kebnekaise - Click 6 mm



Grossglockner - Click 6 mm



Lucania - Click 6 mm