



OAK ANEMONE 226

Oak Anemone features a soft white-wash with subtle grey undertones, delicately balancing the darker wood with the overall even tone of the oak. This creates a sleek, modern design that preserves the warmth and natural beauty of the wood. The smooth, matt lacquered finish enhances the clean, and calm wood design.

	PRODUCT DETAILS		
Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
131257220 / 7393969305334	range		
Plank / Oak	LRV / LRV Std1 / LRV Std2	41 / 3.3 / 6.6	
Matt lacquer / Stained	Warranty	20 years	
	TECHNICAL DROBERTIES	:	
Microbevelled 4-sided, Brushed			7%±2%
187 x 2266 x 13 mm		LIVIDIOD	>500 kg/m ³
24 kg / 7.2 kg			>300 Kg/III
		EN12501 1	Dfl-s1
3.39 m ² / 152.55 m ²			E1
			≤ 5 ppm
Lively			NPD
Woodloc® 5G			0,11W/mK
Floating, Glue-down			Class 1
Yes		EIN35U-Z	
Hardwood / 2.6 mm		CENTE 4 F C 7 C	Compliant
	Slip resistance	CEN/15156/6	NPD
2-3 times	SHEEDIN DANI LAB RYSEEPT		
Pine/Spruce	A+		
Spruce			
	131257220 / 7393969305334 Plank / Oak Matt lacquer / Stained Microbevelled 4-sided, Brushed 187 x 2266 x 13 mm 24 kg / 7.2 kg 3.39 m² / 152.55 m² Lively Woodloc® 5G Floating, Glue-down Yes Hardwood / 2.6 mm 2-3 times Pine/Spruce	Wood Floors / 3-layer parquet 131257220 / 7393969305334 Plank / Oak Matt lacquer / Stained Microbevelled 4-sided, Brushed 187 x 2266 x 13 mm 24 kg / 7.2 kg Moisture content Minimun Mean Density kg/m³ Reaction To Fire Formaldehyde Emission Content PCP Breaking Strength N/mm² Thermal Conductivity Biological Durability Yes Hardwood / 2.6 mm Pine/Spruce Hardness (Brinell) value / range LRV / LRV Std1 / LRV Std2 Warranty TECHNICAL PROPERTIES Moisture content Minimun Mean Density kg/m³ Reaction To Fire Formaldehyde Emission Content PCP Breaking Strength N/mm² Thermal Conductivity Biological Durability CARB2 Slip resistance	Hardness (Brinell) value / 3,7 / 2.2 - 5.9 131257220 / 7393969305334 Plank / Oak Matt lacquer / Stained Microbevelled 4-sided, Brushed 187 x 2266 x 13 mm 24 kg / 7.2 kg Minimun Mean Density kg/m³ Reaction To Fire Formaldehyde Emission EN717-1 Content PCP Centent PCP Centent PCP Centent PCP Floating, Glue-down Yes Hardwood / 2.6 mm Pine/Spruce Hardwood / 2.6 mm Hardness (Brinell) value / 3,7 / 2.2 - 5.9 range TECHNICAL PROPERTIES Moisture content EN13183 Minimun Mean Density kg/m³ Reaction To Fire EN13501-1 Formaldehyde Emission EN717-1 Content PCP CEN/TR14823 Breaking Strength N/mm² EN1533 Thermal Conductivity EN12664 Biological Durability EN350-2 CARB2 Slip resistance CEN/TS15676

DETAILED DESCRIPTION

Calm appearance with moderate color variations and few knots The product includes small and medium sized knots. Knot holes and small cracks are repaired with filler.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection

OAK LUPINE

OAK LAVENDER



OAK ZINNIA