



OAK PRIMROSE

In Oak Primrose, the natural oak is allowed to shine in all its glory—unstained and unaltered—letting the warm tones of the wood penetrate the oiled surface freely. Each board is carefully brushed to enhance the natural grain while gently softening the appearance of knots and cracks.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	131263240 / 7393969305730	range		
Design / Wood Species	Plank / Oak	Warranty	20 years	
Surface treatment /	Oil / Natural	TECHNICAL PROPERTIES	3	
Natural/Stained		Moisture content	EN13183	7%±2%
Design features	Microbevelled 4-sided, Brushed		EINIOIOO	
Width x Length x Thickness	187 x 2420 x 13 mm	——— Minimun Mean Density ——— kg/m³		>500 kg/m³
Weight per package / per	22.5 kg / 7.2 kg	Reaction To Fire	EN13501-1	Dfl-s1
m2		Formaldehyde Emission	EN717-1	E1
Area per package / per	3.17 m ² / 142.65 m ²	Content PCP	CEN/TR14823	≤ 5 ppm
pallet		Breaking Strength N/mm ²	EN1533	NPD
Grading	Dynamic	Thermal Conductivity	EN12664	0,11W/mK
Joint	Woodloc® 5G	Biological Durability	EN350-2	Class 1
Installation method	Floating, Glue-down	CARB2	LINDO-Z	
Floor heating	Yes	-	CENTE 4 F C 7 C	Compliant
Wear leayer material /	Hardwood / 2.6 mm	Slip resistance	CEN/TS15676	NPD
thickness		STREAM DANI LAS ENTERENT		
Resandable	2-3 times	A+		
Core material	Pine/Spruce			
Backside material	Spruce			

DETAILED DESCRIPTION

Naturally occurring wood color variations allowed, ranging from light to dark brown tones. The product features both sound and black knots, as well as natural cracks. The size and number of knots, cracks, and their respective fillings may vary.

Oil: This floor should be oiled immediately after installation.

Colour change: Some muting of colour variation to medium, straw brown.

Packages may contain start and stop boards.

Other products in this collection

OAK LUPINE

OAK LAVENDER



OAK ZINNIA