



OAK PRIMROSE

In Oak Primrose, the natural oak is allowed to shine in all its glory—unstained and unaltered—letting the warm tones of the wood penetrate the oiled surface freely. Each board is carefully brushed to enhance the natural grain while gently softening the appearance of knots and cracks.

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	
Article Number / EAN Code	131263240 / 7393969305730	
Design / Wood Species	1-strip / Oak	
Surface Treatment /	Oil / Natural	
Natural/Stained		
Refining Treatment	Microbevelled 4-sided, Brushed	
Width x Length x Thickness	187 x 2420 x 13 mm	
Weight per package / per	22.5 kg / 7.2 kg	
m2		
Area per package / per	3.17 m ² / 142.65 m ²	
pallet		
Grading	Dynamic	
Joint	Woodloc® 5G	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 2.6 mm	
thickness		
Resandable	2 times	
Core material	Pine/Spruce	
Backside material	Spruce	

|--|

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	20 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant

CEN/TS15676

NPD



Slip resistance



DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, ranging from light to dark brown tones. The product features both sound and black knots, as well as natural cracks. The size and number of knots, cracks, and their respective fillings may vary.

Oil: This floor should be oiled immediately after installation.

Packages may contain start and stop boards.

Other products in this collection



OAK YARROW



OAK ASTER MATT



OAK EDELWEISS



OAK GENTIAN



OAK ASTER OILED



OAK PRIMROSE



OAK LUPINE



OAK LAVENDER



OAK ZINNIA