



OAK LUPINE

A light stain is used to give Oak Lupine its modern, slightly muted look, reminiscent of freshly cut oak timber. The oiled surface, brushed to soften the cracks and knots allows each board to demonstrate the natural wood grain of the material while still retaining the subtilty of this floor – in both its visual and tactile impression.

PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet
Article Number / EAN Code	131265240 / 7393969305754
Design / Wood Species	Plank / Oak
Surface treatment /	Oil / Stained
Natural/Stained	
Design features	Microbevelled 4-sided, Brushed
Width x Length x Thickness	187 x 2420 x 13 mm
Weight per package / per	22.5 kg / 7.2 kg
m2	
Area per package / per	3.17 m ² / 142.65 m ²
pallet	
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 2.6 mm
thickness	
Resandable	2-3 times
Core material	Pine/Spruce

PRODUCT DETAILS

3,7 / 2.2 - 5.9	
20 years	
EN13183	7%±2%
	>500 kg/m³
EN13501-1	Dfl-s1
EN717-1	E1
CEN/TR14823	≤ 5 ppm
EN1533	NPD
EN12664	0,11W/mK
EN350-2	Class 1
	Compliant
CEN/TS15676	NPD
	20 years EN13183 EN13501-1 EN717-1 CEN/TR14823 EN1533 EN12664 EN350-2





DETAILED DESCRIPTION

Backside material

Naturally occurring wood color variations allowed, ranging from light to dark brown tones. The product features both sound and black knots, as well as natural cracks. The size and number of knots, cracks, and their respective fillings may vary.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Spruce

Packages may contain start and stop boards.

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

Other products in this collection

OAK LUPINE

OAK LAVENDER



OAK ZINNIA