



OAK LUPINE

A light stain is used to give Oak Lupine its modern, slightly muted look, reminiscent of freshly cut oak timber. The oiled surface, brushed to soften the cracks and knots allows each board to demonstrate the natural wood grain of the material while still retaining the subtlety of this floor – in both its visual and tactile impression.

PRODUCT DETAILS

| | |
|---|---|
| Product type / Construction | Wood Floors / 3-layer parquet |
| Article Number / EAN Code | 131265240 / 7393969305754 |
| Design / Wood Species | Plank / Oak |
| Surface treatment / | Oil / Stained |
| Natural/Stained | |
| Design features | Microbevelled 4-sided, Brushed |
| Width x Length x Thickness | 187 x 2420 x 13 mm |
| Weight per package / per m ² | 22.5 kg / 7.2 kg |
| Area per package / per pallet | 3.17 m ² / 142.65 m ² |
| Grading | Dynamic |
| Joint | Woodloc® 5G |
| Installation method | Floating, Glue-down |
| Floor heating | Yes |
| Wear leayer material / thickness | Hardwood / 2.6 mm |
| Resandable | 2-3 times |
| Core material | Pine/Spruce |
| Backside material | Spruce |

PRODUCT DETAILS

| | |
|----------------------------------|-----------------|
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |
| Warranty | 20 years |

TECHNICAL PROPERTIES

| | | |
|-------------------------------------|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m ³ |
| kg/m ³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,11W/mK |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

Naturally occurring wood color variations allowed, ranging from light to dark brown tones. The product features both sound and black knots, as well as natural cracks. The size and number of knots, cracks, and their respective fillings may vary.

Oil: This floor should be oiled immediately after installation.


Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.


Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.


Other products in this collection




OAK YARROW



OAK ASTER MATT



OAK EDELWEISS



OAK GENTIAN



OAK ASTER OILED



OAK ANEMONE



OAK DAHLIA MATT




OAK DAHLIA OILED




OAK BUTTERCUP



OAK MARGUERITE



OAK ALP ROSE



OAK PRIMROSE



OAK LUPINE



OAK LAVENDER



OAK ZINNIA



OAK TULIP



OAK IRIS