



OAK LUPINE

A light stain is used to give Oak Lupine its modern, slightly muted look, reminiscent of freshly cut oak timber. The oiled surface, brushed to soften the cracks and knots allows each board to demonstrate the natural wood grain of the material while still retaining the subtilty of this floor – in both its visual and tactile impression.

PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet
Article Number / EAN Code	131265240 / 7393969305754
Design / Wood Species	1-strip / Oak
Surface Treatment /	Oil / Natural
Natural/Stained	
Refining Treatment	Microbevelled 4-sided, Brushed
Width x Length x Thickness	187 x 2420 x 13 mm
Weight per package / per	22.5 kg / 7.2 kg
m2	
Area per package / per	3.17 m ² / 142.65 m ²
pallet	
Grading	Dynamic
Joint	Woodloc® 5G
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material /	Hardwood / 2.6 mm
thickness	
Resandable	2 times
Core material	Pine/Spruce lamella
Backside material	Spruce

PRODU	JCT	DETA	ILS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	20 years	
TECHNICAL PROPERTIES	,	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD





DETAILED DESCRIPTION

Naturally occurring wood colour variations allowed, ranging from light to dark brown tones. The product features both sound and black knots, as well as natural cracks. The size and number of knots, cracks, and their respective fillings may vary.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable colour change over time.

Packages may contain start and stop boards.

Other products in this collection



OAK YARROW



OAK ASTER MATT



OAK EDELWEISS



OAK GENTIAN



OAK ASTER OILED



OAK PRIMROSE



OAK LUPINE



OAK LAVENDER



OAK ZINNIA