



## YUKON CLICK 6 MM

DDODLICT DETAILS

Kährs Luxury Tiles Click floor Yukon is inspired by the soft grey nuances of sun-bleached piers, Yukon features remarkable grain definition in a subtle colour. The clean, calm wood design makes it a perfect floor for contemporary spaces.

PRODUCT DETAILS			
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		
Article Number / EAN Code	LTCLW2102-218 / 7393969110112		
Design	Plank		
Width x Length x Thickness	218 x 1210 x 6 mm		
Weight per package / per	20.6 kg / 9.81 kg		
m2			
Area per package / per	2.11 m <sup>2</sup> / 84.4 m <sup>2</sup>		
pallet			
Joint	Click5G		
I maka Haki a maka kila a al	Floating		
Installation method	Floating		
Floor heating	Yes		
Floor heating	Yes		
Floor heating Wear leayer thickness	Yes 0.55 mm		
Floor heating Wear leayer thickness Warranty	Yes 0.55 mm	23/33/42	
Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES	Yes 0.55 mm 30 years	23/33/42 No visible damage/Change	
Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES Application	Yes 0.55 mm 30 years EN ISO 10874		
Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES Application Effect of furniture leg	Yes 0.55 mm 30 years EN ISO 10874	No visible damage/Change	

Reaction To Fire	EN13501-1	Bfl-s1
Formaldehyde Emission	EN717-1	E1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN		< 0.2 mm (*with
ISO 24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable (25.000 cycles)
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 <b>Δ</b> Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











## **DETAILED DESCRIPTION**

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

www.kahrs.com | ©Kährs **Descriptions & Imagery** All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

## Other products in this collection







HANMER CLICK



WHINFELL CLICK 6 MM



YUKON CLICK



TIVEDEN CLICK

WENTWOOD CLICK