



YUKON CLW 218

Kährs Rigid Click Luxury Tiles floor Yukon is inspired by the soft grey nuances of sun-bleached piers. Yukon features remarkable grain definition in a subtle colour. The clean, calm wood design makes it a perfect floor for contemporary spaces.

PRODUCT DETAILS

| | |
|--------------------|---------------------|
| Article Number | LTCLW2102-218 |
| Dimensions | 218 x 1210 mm |
| Weight per Package | 20.6 kg |
| Area per Package | 2.1 m ² |
| Area per pallet | 84.5 m ² |
| | Click 6 mm |

DETAIL DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

FACTS

| | |
|------------|-------------------|
| Design | Wood design |
| Range | Luxury Tiles |
| Collection | Breeze Collection |
| Joint | Click5G |




TECHNICAL PROPERTIES

| | | | |
|--------------------------------|----------------|-------------------------------|--|
| Application | EN ISO 10874 | 23/33/42 | |
| Emission of formaldehyde | | E1 | |
| Reaction To Fire | EN13501-1 | Bfl-s1 | |
| Formaldehyde Emission | EN717-1 | E1 | |
| Thermal Resistance R-Value | | 0.035 (m2K/W) | |
| Residual indentation | EN ISO 24343-1 | < 0.2 mm (*with underlayment) | |
| Dimensional stability | EN ISO 23999 | < 0.1 % | |
| Colour fastness | EN ISO 105-B02 | ≥ 6 | |
| Slip resistance | EN 13893 | DS (>0.3) | |
| Slip resistance | DIN 51130 | R10 | |
| Statical electrical propensity | EN 1815 | < 2 kV (antistatic) | |

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

TECHNICAL PROPERTIES

| | | | |
|----------------------------------|---------------|-------------------------------|---|
| Scratch resistance | EN16094 | Pass with good results |  |
| Chemical resistance | EN ISO 26987 | Pass with good results |  |
| Resistance to bacteria and fungi | | Good | |
| Impact sound reduction | EN ISO 10140 | 20 ΔLw dB (IXPE underlayment) |  |
| Commercial usage classification | EN 14354:2017 | Class 33 | |

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



Other products in this collection



Fontin - Click 6 mm



Hanmer - Click 6 mm



Whinfell - Click 6 mm



Yukon - Click 6 mm



Tiveden - Click 6 mm



Wentwood - Click 6 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.