



TIVEDEN CLICK 6 MM

Kährs Rigid Click Luxury Tiles floor Tiveden has deep brown nuances inspired by the bark of pines, adding a touch of elegance to any interior. The grey undertones enhance the calm, subtle wood design grading.

| PRODUCT DETAILS | | |
|-----------------------------|---|----------|
| Product type / Construction | Luxury Vinyl Tiles and Planks / Click SPC LVT | |
| Article Number / EAN Code | LTCLW2005-218 / 7393969110143 | |
| Design | 1-strip | |
| Width x Length x Thickness | 218 x 1210 x 6 mm | |
| Weight per package / per | 20.6 kg / 9.81 kg | |
| m2 | | |
| Area per package / per | 2.11 m ² / 84.4 m ² | |
| pallet | | |
| Joint | Click5G | |
| Installation method | Floating | |
| Floor heating | Yes | |
| Wear leayer thickness | 0.55 mm | |
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | | |
| Application | EN ISO 10874 | 23/33/42 |
| Emission of formaldehyde | | E1 |
| Reaction To Fire | EN13501-1 | Bfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |

| TECHNIC/LET NOT ENTILS | | |
|----------------------------|----------------|--------------------------|
| Thermal Resistance R-Value | | 0.035 (m2K/W) |
| Residual indentation | EN ISO 24343-1 | < 0.2 mm (*with |
| | | underlayment) |
| Dimensional stability | EN ISO 23999 | < 0.1 % |
| Colour fastness | EN ISO 105-B02 | ≥ 6 |
| Slip resistance | EN 13893 | DS (>0.3) |
| Slip resistance | DIN 51130 | R10 |
| Statical electrical | EN 1815 | < 2 kV (antistatic) |
| propensity | | |
| Scratch resistance | EN16094 | Pass with good results |
| Chemical resistance | EN ISO 26987 | Pass with good results |
| Effect of castor chair | EN 425 | Suitable (25.000 cycles) |
| Resistance to bacteria and | | Good |
| fungi | | |
| Impact sound reduction | EN ISO 10140 | 20 Δ Lw dB (IXPE |
| | | underlayment) |
| Commercial usage | EN 14354:2017 | Class 33 |
| classification | | |











DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Other products in this collection







HANMER CLICK



WHINFELL CLICK



YUKON CLICK



TIVEDEN CLICK



WENTWOOD CLICK