



WHINFELL CLICK 6 MM

Kährs Luxury Tiles Click floor Whinfell has a spectrum of warm brown and grey tones inspired by cliffs of the archipelago. Whinfell, with its calm wood design and luxurious, natural impression gives any space a grand makeover.

PRODUCT DETAILS			
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		
Article Number / EAN Code	LTCLW2004-218 / 7393969110129		
Design	Plank		
Width x Length x Thickness	218 x 1210 x 6 mm		
Weight per package / per	20.6 kg / 9.81 kg		
m2			
Area per package / per	2.11 m ² / 84.4 m ²		
pallet			
Joint	Click5G		
Installation method	Floating		
- 	Floating Yes		
Installation method			
Installation method Floor heating	Yes 0.55 mm	ntial/15 years commercial	
Installation method Floor heating Wear leayer thickness	Yes 0.55 mm	ntial/15 years commercial	
Installation method Floor heating Wear leayer thickness Warranty	Yes 0.55 mm	ntial/15 years commercial 23/33/42	
Installation method Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES	Yes 0.55 mm 30 years residen		
Installation method Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES Application	Yes 0.55 mm 30 years residen	23/33/42	

Formaldehyde Emission	EN717-1	E1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN		< 0.2 mm (*with
ISO 24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











DETAILED DESCRIPTION

PRODUCT DETAILS

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Descriptions & Imagery www.kahrs.com | ©Kährs All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items

Other products in this collection







HANMER CLICK



WHINFELL CLICK



YUKON CLICK



TIVEDEN CLICK

WENTWOOD CLICK