



OULANKA CLICK 6 MM

Kährs Luxury Tiles Click floor Oulanka was inspired by the light gold and brown tones of wheat fields swaying in the wind, one of our most popular LVT floors. Authentic wood colours and realistic characterful features such as knots and cracks enhance the natural look of this floor.

PRODUCT DETAILS			TECHNICAL F
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		Formaldehyde
Article Number / EAN Code	LTCLW2110-218 / 7393969110013		Thermal Resist
Design	Plank		Residual inden
Width x Length x Thickness	218 x 1210 x 6 mm		ISO 24343-1
Weight per package / per	20.6 kg / 9.81 kg		Dimensional st
m2			Colour fastnes
Area per package / per	2.11 m ² / 84.4 m ²		Slip resistance
pallet			Slip resistance
Joint	Click5G		Statical electric
Installation method	Floating		propensity
Floor heating	Yes		Scratch resista
Wear leayer thickness	0.55 mm		Chemical resis
Warranty	30 years residential/15 years commercial		Effect of castor
TECHNICAL PROPERTIES			Resistance to b
Application	EN ISO 10874	23/33/42	fungi
Effect of furniture leg	EN ISO 16581	No visible damage/Change	Impact sound
Emission of formaldehyde	FIN 130 10301	F1	_
Reaction To Fire	EN13501-1	Bfl-s1	Commercial us
Reaction to Fife	LIVIOOUI-I	ווים וויים	— classification

TECHNICAL PROPERTIES		
Formaldehyde Emission		

Formaldehyde Emission	EN717-1	E1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN		< 0.2 mm (*with
ISO 24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and		Good
- fungi		
Impact sound reduction	EN ISO 10140	20 Δ Lw dB (IXPE
_		underlayment)
Commercial usage	EN 14354:2017	Class 33
- classification		











DETAILED DESCRIPTION

DDODLICT DETAILS

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Descriptions & Imagery

Other products in this collection







SAPO CLICK



SAXON CLICK



REDWOOD CLICK



SAREK CLICK



OULANKA CLICK



TAIGA CLICK