



OULANKA CLW 218

DDODLICT DETAILS

Kährs Luxury Tiles Click floor Oulanka was inspired by the light gold and brown tones of wheat fields swaying in the wind, one of our most popular LVT floors. Authentic wood colours and realistic characterful features such as knots and cracks enhance the natural look of this floor.

PRODUCT DETAILS			TECHNICAL PROPER
Product type / Construction	Luxury Vinyl Tiles / Click 6 mm		Formaldehyde Emission
Article Number / EAN Code	LTCLW2110-218 / 7393969110013		Thermal Resistance R-V
Design	Wood design		Residual indentation EN
Width x Length x Thickness	218 x 1210 x 6 mm		ISO 24343-1
Weight per package / per	20.6 kg / 9.81 kg		Dimensional stability
m2			Colour fastness
Area per package / per	2.1 m ² / 84.5 m ²		Slip resistance
pallet			Slip resistance
Joint	Click5G		Statical electrical
Installation method	Floating		propensity
Floor heating	Yes		Scratch resistance
Wear leayer thickness	0.55 mm		Chemical resistance
Warranty	30 years reside	ntial/15 years commercial	Effect of castor chair
TECHNICAL PROPERTIES			Resistance to bacteria a
	EN ISO 10874	23/33/42	– fungi
Application			Impact sound reduction
Effect of furniture leg	EN ISO 16581	No visible damage/Change	_
Emission of formaldehyde		E1	- Commorcial usage
Reaction To Fire	EN13501-1	Bfl-s1	Commercial usage
			 classification

TECHNICAL F	PROPERTIES
-------------	------------

Formaldehyde Emission	EN717-1	E1
Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation EN		< 0.2 mm (*with
ISO 24343-1		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and		Good
- fungi		
Impact sound reduction	EN ISO 10140	20 ΔLw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
– classification		











DETAILED DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. Surface treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Other products in this collection



Aspen - Click 6 mm



Sapo - Click 6 mm



Saxon - Click 6 mm



Redwood - Click 6 mm



Sarek - Click 6 mm



Oulanka - Click 6 mm



Taiga - Click 6 mm