



## **OULANKA CLW 218**

PRODUCT DETAILS

Kährs Rigid Click Luxury Tiles floor Oulanka, one of our most popular LT floors, was inspired by the light gold and brown tones of wheat fields swaying in the wind. Authentic wood colours and realistic characterful features such as knots and cracks enhance the natural look of this floor.

PRODUCT DETAILS		
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT	
Article Number / EAN Code	LTCLW2110-218 / 7393969110013	
Design	Tile Design	
Width x Length x Thickness	218 x 1210 x 6 mm	
Weight per package / per	20.6 kg / 9.81 kg	
m2		
Area per package / per	2.1 m <sup>2</sup> / 84.5 m <sup>2</sup>	
pallet		
Joint	Click5G	
Installation method	Floating	
Installation method Floor heating	Floating Yes	
Floor heating	Yes	s commercial
Floor heating Wear leayer thickness	Yes 0.55 mm	s commercial
Floor heating Wear leayer thickness Warranty	Yes 0.55 mm	commercial 23/33/42
Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES	Yes 0.55 mm 30 years residential/15 years	
Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES Application	Yes 0.55 mm 30 years residential/15 years	23/33/42
Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES Application Emission of formaldehyde	Yes 0.55 mm 30 years residential/15 years EN ISO 10874	23/33/42 E1

TECHNICAL F	PROPERTIES
-------------	------------

Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 <b>Δ</b> Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











## **DETAILED DESCRIPTION**

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

## Other products in this collection



ASPEN - CLICK 6 MM



SAPO - CLICK 6 MM



SAXON - CLICK 6 MM



REDWOOD - CLICK 6 MM



SAREK - CLICK 6 MM



OULANKA - CLICK 6 MM



TAIGA - CLICK 6 MM