



## **OULANKA CLICK 6 MM**

Kährs Rigid Click Luxury Tiles floor Oulanka, one of our most popular LT floors, was inspired by the light gold and brown tones of wheat fields swaying in the wind. Authentic wood colours and realistic characterful features such as knots and cracks enhance the natural look of this floor.

PRODUCT DETAILS			
Product type / Construction	Luxury Vinyl Tiles and Planks / Click SPC LVT		
Article Number / EAN Code	LTCLW2110-218 / 7393969110013		
Design	1-strip		
Width x Length x Thickness	218 x 1210 x 6 mm		
Weight per package / per	20.6 kg / 9.81 kg		
m2			
Area per package / per	2.11 m <sup>2</sup> / 84.4 m <sup>2</sup>		
pallet			
Joint	Click5G		
Installation method	Floating		
-	Floating Yes		
Installation method			
Installation method Floor heating	Yes	s commercial	
Installation method Floor heating Wear leayer thickness	Yes 0.55 mm	s commercial	
Installation method Floor heating Wear leayer thickness Warranty	Yes 0.55 mm	23/33/42	
Installation method Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES	Yes 0.55 mm 30 years residential/15 years		
Installation method Floor heating Wear leayer thickness Warranty TECHNICAL PROPERTIES Application	Yes 0.55 mm 30 years residential/15 years	23/33/42	

TECHN	IICAL	PROP	ERTIES

Thermal Resistance R-Value		0.035 (m2K/W)
Residual indentation	EN ISO 24343-1	< 0.2 mm (*with
		underlayment)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)
Slip resistance	DIN 51130	R10
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Scratch resistance	EN16094	Pass with good results
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and		Good
fungi		
Impact sound reduction	EN ISO 10140	20 <b>∆</b> Lw dB (IXPE
		underlayment)
Commercial usage	EN 14354:2017	Class 33
classification		











## **DETAILED DESCRIPTION**

PRODUCT DETAILS

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

## Other products in this collection







SAPO CLICK



SAXON CLICK



REDWOOD CLICK



SAREK CLICK



OULANKA CLICK



TAIGA CLICK