



OULANKA CLW 218

Kährs Rigid Click Luxury Tiles floor Oulanka, one of our most popular LT floors, was inspired by the light gold and brown tones of wheat fields swaying in the wind. Authentic wood colours and realistic characterful features such as knots and cracks enhance the natural look of this floor.

PRODUCT DETAILS

| | |
|--------------------|---------------------|
| Article Number | LTCLW2110-218 |
| Dimensions | 218 x 1210 mm |
| Weight per Package | 20.6 kg |
| Area per Package | 2.1 m ² |
| Area per pallet | 84.5 m ² |
| | Click 6 mm |

FACTS

| | |
|---------------------|--|
| Design | Wood design |
| Range | Luxury Tiles |
| Collection | Nature Collection |
| Joint | Click5G |
| Floor heating | Yes |
| Warranty | 30 years residential/15 years commercial |
| | 6 mm |
| Installation method | Floating |

TECHNICAL PROPERTIES

| | | |
|-----------------------------------|--|--|
| Application | EN ISO 23/33/42 10874 | |
| Emission of formaldehyde | E1 | |
| Reaction To Fire | EN13501- Bfl-s1 1 | |
| Formaldehyde Emission | EN717-1 E1 | |
| Thermal Resistance R-Value | 0.035 (m2K/W) | |
| Residual indentation | EN ISO 24343-1 < 0.2 mm (*with underlayment) | |
| Dimensional stability | EN ISO 23999 < 0.1 % | |
| Colour fastness | EN ISO 105-B02 ≥ 6 | |
| Slip resistance | EN 13893 DS (>0.3) | |
| Slip resistance | DIN 51130 R10 | |
| Statistical electrical propensity | EN 1815 < 2 kV (antistatic) | |




DETAIL DESCRIPTION

For adhesive-free installation in homes and public spaces. Maximum durability and stability through the rigid core and the unique 5G locking system, enabling easy installation by clicking the tiles together. Made from rigid core virgin vinyl, they are phthalate-free and have IXPE sound reducing backing, effectively controlling noise. The surface is treated with a strong ceramic coating resistant to wear, scratching and water. Can be installed on an existing floor, ideal for renovation projects.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

TECHNICAL PROPERTIES

| | | | |
|----------------------------------|---------------|-------------------------------|---|
| Scratch resistance | EN16094 | Pass with good results |  |
| Chemical resistance | EN ISO 26987 | Pass with good results |  |
| Resistance to bacteria and fungi | | Good | |
| Impact sound reduction | EN ISO 10140 | 20 ΔLw dB (IXPE underlayment) |  |
| Commercial usage classification | EN 14354:2017 | Class 33 | |

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



Other products in this collection



Aspen - Click 6 mm



Sapo - Click 6 mm



Saxon - Click 6 mm



Redwood - Click 6 mm



Sarek - Click 6 mm



Oulanka - Click 6 mm



Taiga - Click 6 mm

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.